

# The Perfect Upholstery Corner



## Materials and Supplies:

Items	Rowley Item#
Upholstery Air Stapler	NSG10
Staples	NS33/E or NS32/E
Regulator	MH26 or MH28
Safety Glasses	SG01 or SG02



## Step-by-Step

Read instructions for FirmaFlex™ Bendable Fiber Board which can be found at [www.RowleyCompany.com](http://www.RowleyCompany.com) under Product Instructions.

1. Staple the fabric to within 2" from the corner, on both sides of the corner (Photo 1).



Photo 1



Photo 2



Photo 3

2. Pull one side of the fabric (the side that is on the side of the piece) around the corner and up onto the top of the piece, following the grain of the fabric. Pull the fabric taut (Photo 2).
  - a. If you look at the back of the piece, the fabric from the first step of the corner fold creates a 45° angle when folded down. You can staple this down now, but it is not absolutely necessary because you will catch this fabric in your final staple.
3. Fold the excess fabric from the top under the fold and pull taut (Photo 3). This fold should be flat on the back of the piece. Staple through both the first and second layer of the fold at this time.
  - a. Staple at a 45° angle, high up on in the corner (Photo 4). The staple needs to catch both layers of folds. This staple will be hidden with the next step.

4. Fold the top layer of the stapled fabric back onto itself to cover the previous staple. Staple this flap down about 2” from the corner so that the staple will be hidden with then next layer, be it Cambric or fabric (Photo 5).



Photo 4



Photo 5

### How to Eliminate Bulk in the Corner:

1. Fold the fabric into a Perfect Upholstery Corner. Pinch the final fold (Photo 6). Holding the fold, cut away any fabric that would have been tucked underneath the final fold (Photo 7).
  - a. Photo 8 shows the cut away of the fabric – if it were unfolded.
2. Fold the fabric back into place (Photo 9) and staple.



Photo 6



Photo 7




Photo 8



Photo 9

### Tips and Tricks:

- Use a regulator to help dress the corner.
- When eliminating bulk, staple the first side down (Photo 8) to hold the fold tension in place.