



Motorized Shade Systems

Quick Order Checklist



✓ Motor

- R-TEC Automation®: Li-ion Battery; or Automate®: Li-ion Battery, DC or Basics
- 25 mm, 28 mm or 35 mm size; various lengths
- Shade weight determines motor size - refer to the chart

✓ Motor Power

- Li-ion Battery Motors: Battery Chargers, Extensions or Solar Panel
- DC Motors: Battery Pack, Battery Tube, Power Supply or 18 Channel Power Distributor

✓ Aluminum Roller Tube

- 1 ¼", 1 ½" or 2" diameter
- 4', 6', 8', 12' or 16' length; splice with Skyline Easy Link System

✓ Drive Set Kit (must match motor type)

- Crown & Drive Set, Shaft Clip and End Pin

✓ Skyline Mount Brackets & Covers

- Narrow option available
- Bracket Covers in White, Black, or Satin Nickel

✓ Roman Lift Band Option Components

- Translucent Woven Buckram
- Round Fiberglass Ribs + Rib Guides (Center Supports & End Caps) recommended, but alternative rib options include Round Acrylic Ribs, Round Plastic Ribs, or Flat Fiberglass Ribs
- Consider Rib Tape
- Weight Bar - 3/8" Solid Steel Rod or Flat

✓ Roman Lift Cord Option Components

- Roller Tube Clips (1 ¼", 1 ½" and 2" sizes only)
- 0.9 mm Encased Lift Cord Shroud Tube
- Requires one Sew-On Ring per column of lift
- Ribs for structure and Rib Tape
- Weight Bar - 3/8" Solid Steel Rod or Flat
- Consider Cord Adjuster Orbs

✓ Roller Option Components

- Laminating Adhesive
- Room Darkening Shade Cloth
- Wood Shade Slat or Bottom Rail

✓ Control & Integration

- Remote Controls, Switches, Wi-Fi Hubs & Apps

R-TEC AUTOMATION®

AUTOMATE®